



TECHNISTAR S6 Int. Edt.

HDTV digital satellite receiver with USB-PVR function

EAN	Item no.	Device (W x H x D)	Colour
4019588647176	0006/4717	22.00 x 4.50 x 17.70 cm	black

CONNECTIONS	Menu locking: Yes	Audio-Formats: MP3, WAV, AAC, FLAC, MP2, OGG, DDAC3, AIFF
HDMI (out): 1	Control panel lock: Yes	Picture-Formats: JPEG, BMP, GIF, PNG, TIFF
USB: 1 (USB 2.0)	Integrated LED clock: Yes	Video-Codects: MPEG-4, MPEG-2, H.264
Common Interface Plus (CI+): Yes	Selectable start source: Yes	Video-Formats: MP4, M4V, MKV, MOV, MPG, TS, TS4, Xvid, M2TS, AVI, ASF
Smartcard reader: Yes	Selectable start channel: Yes	TECHNISAT CONNECT
Digital electric audio output: Yes	LNB	Control: Yes
audio/video output analog (3.5 mm jack): Yes TechniSat specific adapter set necessary (available at 0000/3649)	Vertical power supply: 14 V	SFI: Yes
Ethernet 10/100 (RJ-45): Yes	Horizontal power supply: 18 V	TUNER
F socket: Yes	LNB modulation: 22 kHz	Tuner type: DigitalSat
DC IN: 1	LNB power supply: 400 mA	DVB-S tuner: 1
DECODER	DiSeqC: 1.0 / 1.2	Single Cable Solution (SatCR): SCR1 = EN50494, SCR2 = EN50607
Video decoder: MPEG-2 MP@HL/ML, H.264/MPEG-4 AVC	OTHER FEATURES	Satellite radio: Yes
Audio decoder: MPEG-1 & MPEG-2 Layer I, II, III	Total programme memory: 9999	Internet radio: Yes
DECRYPTION SYSTEM	Regional channel selection: Yes	Reception on: HD-TV, SD-TV, DVB radio
Conax: Yes	Internet radio: Yes	TECHNIROUTER ready: Yes
CI+: Yes (v1.3)	OSD languages: Danish, German, English, French, Greek, Italian, Dutch, Norwegian, Polish, Portuguese, Russian, Swedish, Spanish, Czech, Turkish, Hungarian	TUNER - SAT
DISPLAY	PICTURE FUNCTIONS	Reception range: 950 ... 2150 MHz
Type: 7 segment, 4 digits, white	Freeze frame: Yes	Viterbi rates: 1/2, 2/3, 3/4, 5/6, 7/8
ENVIRONMENT	SD: Yes	DVB-S: QPSK
Ambient temperature: 5 ... 35 °C	HD: Yes	DVB-S: 2 ... 45 Mbaud
Humidity: 10 ... 75 %	1080p: Yes	DVB-S2: 8PSK - QPSK
Storage temperature: -20 ... 60 °C	1080i: Yes	DVB-S2: 2 ... 45 Mbaud
HANDLING/COMFORT	720p: Yes	FEC: Viterbi and Reed-Solomon
Page memory: 1000	576p: Yes	MULTIMEDIA
Teletext subtitles: Yes	576i: Yes	DVR function: Ja
Media Player: Yes	POWER CONSUMPTION	DVR storage medium: via USB
Sleep timer: Yes	In operation: 4.8 W without LNB	Timeshift: Yes
Teletext: Yes	Standby: < 0,3 W	Recordings edition function: Yes
Clock: Yes	POWER SUPPLY	Recordings folder management: Yes
HOTEL MODE	Nominal voltage: 230 V	TECHNISAT ADDED VALUE SERVICES
Protected access to hotel mode: Yes	Frequency: 50 Hz	AUTOINSTALL: Yes
Customisable start screen: Yes	Mains adapter: external DC 12V/2A	SCOPE OF DELIVERY
Lockable volume: Yes	SUPPORTED FORMATS & CODECS	

KEYFEATURES

"SiehFern INFO" (SFI)

ISIPRO

TechniMatic

AutoInstall

TechniFamily

DVRready

Perfect Recording

Pay TV ready

Universal Plug And Play (UPnP)

Editing function

TechniRouter-ready